

## PRODUCT DETAILS

## **SLACK WAX**

Slack Wax (also called petrolatum) is a petroleum derivative with different kinds of paraffinic contents within in addition to ISO - Paraffin hydrocarbons. It is made as a by-product of Base Oil Manufacturing.

Slack Wax can be applied in several industries acting as waterproofing agent and blending components including Wax Emulsion, Candle, Paraffin and Textile manufacturing.



Slack Wax Specifications vary from each producer to other, but there are general aspects to understand the quality of the product demonstrated in the below table:

| Slack Wax General Specifications |             |       |      |       |      |       |  |
|----------------------------------|-------------|-------|------|-------|------|-------|--|
| Properties                       | Test method | H-8   | H-12 | H-16  | L-14 | SW-40 |  |
| Oil Content (Weight %)           | D-721       | 12-16 | 8-12 | 12-16 | 14   | 35    |  |
| Congealing Point (°C)            | D-938       | 57    | 59   | 57    | 54   | 61    |  |

| Available Packaging |                     |  |  |  |
|---------------------|---------------------|--|--|--|
| Package Type        | Quantity per 20 FCL |  |  |  |
| New Steel Drum      | 80 Drums/20 FCL     |  |  |  |
| Flexi Bag           | 21-22 MT            |  |  |  |



Zista Group supplies different grades of Slack Wax worldwide while guarantying the aspects of quality for each shipment. The steady supply of Slack Wax by Zista Group is direct from Sepehan, Pars Oil and other certified refineries from Iran.

For more information please do not hesitate to contact us; info@zistalube.com